



Atalla AT1000



Atalla AT1000 is a FIPS 140-2 Level 3 & PCI PTS v3 certified payment Hardware Security Module (HSM) used to protect sensitive data and associated keys for non-cash retail payment transactions, cardholder authentication, and cryptographic keys.

Product Highlights

Atalla AT1000 is used by all the leading players in the payment ecosystem – issuers, acquirers, payment processors and payment networks across the globe – supporting the following use cases:

- PIN Processing
- 3-D Secure
- Card / User Verification
- ATM Interchange
- Data Integrity
- Processing Transaction Data
- Data Encryption / Decryption
- Initialize Remote Payment Devices
- PIN Translations
- Payment Card Verification, Production and Personalization
- Electronic Funds Interchange (EFTPOS, ATM)
- Cash-Card Reloading
- EMV Transaction Processing
- Key Generation and Injection
- ATM Remote Key Loading
- End-to-End Encryption (E2E) of credentials for Internet and Mobile Banking

The next-generation Atalla AT1000 HSM host commands are fully backward compatible with its predecessors, incorporating more than three decades of expertise – enabling co-existence and easy migration.





Key Features

Key Differentiators

- The unique flexible approach to HSM configuration and key management that enables a remote workflow-based model meeting the PCI Dual Control Requirement without the need to have all of the individual officers physically present
- Robust backup/restore capability with a user-configurable policy to specify M of N smartcards required for a restore
- Full multi-domain key and policy enforcement enables enterprises to create and manage multiple segregated digital keys per business need while applying policy enforcement to govern the key on the HSM
- In-field scalable performance, highly scalable with more than 10,000 TPS in a single device

- Integrates with all major payment and switching applications for easy integration into your existing infrastructure (managed as an IT Security device)
- Integrated with Micro Focus Voltage SecureData product portfolio to protect the data encryption keys
- Close integration with HPE NonStop Systems to provide a fully fault-tolerant and redundant payment solution
- Backwards compatible with the previous generation Atalla HSMs
- Multiple MFK Support – up to 10 partitions per HSM
- 4x1Gbps NIC – Supports Teaming
- TLS protected and authenticated sessions with host application – no performance impact
- Optional customization

Security Certifications

- PCI - PTS - HSM v3.0 certified (certificate #4-70041)
- FIPS 140-2 Level 3 certified (certificate #3059)

Physical Security

- Rack-mountable (1U), physically fortified form factor with double-locking bezel and Medeco pick-resistant locks
- Dual redundant power supplies
- Out-of-range temperature and voltage detection
- Low-battery voltage detection

Logical Security

- Dual control
- Industry-standard Atalla Key Block (AKB) key management technology for AES and TDEA or 3DES key management

- Advanced security architecture that prevents retrieval of PINs, keys, and other sensitive data in clear text form
- Automated and manual key management options
- Encrypted, convenient configuration, management, and key loading via Atalla Secure Configuration Assistant (no clear text passing of keys or key components)
- ATM key initialization and remote key loading (RKL)
- PIN security and key management implemented within a tamper-resistant hardware security module perimeter for protection against manipulation

Performance

- Rated at 10,000, 1080, 280, and 80 TPS (PIN translations per second)



HSM Functionalities

- **Symmetric Key management:** TR-31, X9.24 (incl. AES and TDES DUKPT), X9.17, APACS 40/70
- **Asymmetric Key management:** TR-34, legacy RSA keying protocols including those for Diebold and NCR ATMs
- **Data Encryption:** AES, RSA OAEP, DES/

TDES (X3.92, ISO 10126-2, X9.52)

- **Message authentication:** CMAC (AES and TDES), HMAC (SHA1 and SHA256), CBC MAC (ANSI X9.9, ANSI X9.19, ISO 9797-1, ISO 16609, ISO 9807)
- **Digital signatures:** RSA PKCS#1 v1.5 and ISO 9796-2

- **PIN management and security:**

ANSI X9.8/ISO 9564 PIN blocks 0 to 4, plus legacy techniques

- **PIN verification:** IBM 3624, PVV, Atalla Bi-Level DES, Diebold, NCR

- **Payment Card Processing:** MasterCard CVC, Visa CVV, American Express CSC, MasterCard CVC3,

Visa dCVV, Discover DCVV, American Express Expresspay, Visa Cloud based payments

- EMV-based smart card support
- **End-to-End Encryption (E2E):** Supports Internet and Mobile Banking credentials generation/verification/reset operations



More About Atalla Key Block

Atalla Key Block is the advanced key management complement to the Atalla HSM models. Leading financial industry independent software vendors (ISVs) have embraced Atalla Key Block. It has also been adopted as part of the industry-standard ANSI X9.24 Part 1-2009 Retail Financial Services Symmetric Key Management Part 1: Using Symmetric Techniques and ANSI X9.24 Part 2-2006 Retail Financial Services Symmetric Key Management Part 2: Using Asymmetric Techniques for Distribution of Symmetric Keys.



Technical Specifications



Physical Dimensions

- **Height:**
1.69 inches (4.3 cm)
- **Depth:**
30.87 inches (78.4 cm)
- **Width:**
19.01 inches (48.3 cm)
- **Weight:**
36.3 pounds (16.5 kg)
- **Controls:**
Power on/off switch,
unit ID switch,
LCD control panel



Connectivity

- **Communications Ethernet:**
TCP/IP, TLS 1.2 (only)
- **Connection:**
10/100/1000BASE-T
(RJ45) auto-sensing
- **Communication Protocols:**
TCP – host and management commands
UDP – host commands



Electrical

- **Rated input voltage:**
100 to 127 VAC
200 to 240 VAC
- **Rated input power:**
480 W at 100 VAC
480 W at 200 VAC
- **Rated input current:**
4.8 A at 100 VAC
2.4 A at 200 VAC
- **BTUs per hour:**
1638 at 100 VAC
1638 at 200 VAC
- **Rated input frequency:**
50 Hz to 60 Hz
- **Rated steady-state power:**
250 W at 100 VAC
250 W at 200 VAC
- **Maximum peak power:**
480 W at 100 VAC
480 W at 200 VAC



Operating Environment

- **Temperature:**
10°C to 35°C
(50°F to 95°F)
- **Relative humidity:**
5% to 95%
Non-condensing



Certification/Compliance

- **Safety:**
UL, CSA, CE, TUV, GS,
EAC, EK, CCC, BIS, BSMI,
BIS, RCM
- **Emissions:**
FCC Class A, VCCI
- **Environmental:**
RoHS 2.07





EMEA

UTIMACO IS GmbH

📍 Germanusstraße 4
52080 Aachen,
Germany

☎ +49 241 1696 200

✉ hsm@utimaco.com

Americas

UTIMACO Inc.

📍 900 E Hamilton Ave.,
Suite 400
Campbell, CA 95008,
USA

☎ +1 844 UTIMACO

✉ hsm@utimaco.com

APAC

UTIMACO IS Pte Limited

📍 50 Raffles Place,
Level 19,
Singapore Land Tower,
Singapore 048623

☎ +65 6631 2758

✉ hsm@utimaco.com

For more information about UTIMACO HSM products, please visit:

id-3.co.uk/utimaco

hsm.utimaco.com

© UTIMACO IS GmbH 08/20

UTIMACO® is a trademark of UTIMACO GmbH. All other named Trademarks are Trademarks of the particular copyright holder. All rights reserved. Specifications are subject to change without notice.

ID-3



> id-3.co.uk <



Security Standards Council

QUALIFIED INTEGRATORS AND RESELLERS